



PRODUCT SPECIFICATION - APPLICATION & USE

PRODUCT NAME: **FREEWAY**

GENERAL DESCRIPTION: A biological fat and grease digester.

USE FOR WHICH PRODUCT IS INTENDED: To maintain grease traps, drains and kitchen hoods.

SPECIAL EQUIPMENT REQUIRED: Dosing meter for grease traps. Hand spray for kitchen hoods.

METHOD AND CONDITIONS OF USE:

GREASE TRAPS:

1. Clean out grease trap prior to treatment.
2. Seed the grease trap by adding initial dose direct to trap, dosage rate - 1.5 litres of FREEWAY per cu. Metre of volume of trap.
3. Maintenance dosage to be added daily to drains upstream

No. OF MEALS PER DAY	DAILY MINIMUM DOSE
400 - 500	400 ml
800	650 ml
1000	800 ml
1500	1.2 litres
2000	1.5 litres

MAINS - FOR STANDARD SIZE DRAINS:

SEEDING - 200 ML INITIAL DOSE

REGULAR MAINTENANCE - 100 ML / DAY

EXTRACTOR HOODS:

For best results, initial treatment should follow a cleandown.

1. Thoroughly spray neat product onto the surfaces of filter elements before reassembling.
2. For regular maintenance spray neat product onto the surfaces of hoods either before or after work on a daily basis.
3. Once each month remove filters and wipe clean with hot water. Repeat procedure as in 1.

METHOD OF CONTROL: Visual examination of conditions of trap or hood.